




1. Sinking caissons
(Concrete rings).

2. Reinforced concrete or ferrocement cast *in situ* above waterline, concrete rings sunk below waterline.

3. Masonry lining of burnt bricks above waterline, caisson made of blocks with cutting ring below waterline.

4. Galvanized iron rings bolted together as a temporary measure for emergencies.



This Technical Brief concentrates on sinking caissons as one of the most useful methods. It is safe, efficient and economical where the cost of equipment, notably the steel moulds for casting the concrete rings, can be spread over several wells. The skill of the well-diggers will also build up with experience. A tube of rings is built upwards and is

B

Know the community, meet leaders, talk to the women who will be using the well. Involve the community, which should provide the money for materials, and provide skilled and unskilled labour.


Look at existing water sources. If you are going to convert an existing water hole, it should be well away from pit latrines but convenient to reach.

Check all time 5 nien 12i44asonng wateln evces

6mm or 8mm



VIII
or

Suspend the first ring on ropes as shown, using about 15 people to hold the ropes to be safe, and lower it until it sits level at the bottom of the hole.



Continue digging inside the ring. Wells can be de-watered by bucket and hard work, or by a small diesel, petrol or hand operated diaphragm pump.

Lower further rings as the first one sinks. The deeper the well the larger the amount of storage and in some cases infiltration. The well is used during the day and refills at night.



Workers should wear helmets and buckets should be tethered while they are down the hole. Keep engine-driven pumps away from the hole to avoid the build-up of toxic fumes.


B

Your well can now provide fresh water, as long as it is properly finished.

The surrounds soon get dirty, allowing contaminated water to seep back into the well. Puddles of spilt water transmit hookworm through feet.

So disinfect the well with chlorine solution or bleaching powder. Mound up the earth around the rings so that water drains away from the well, and compact the earth firmly.

Cross-section of this slab is shown below



L

P

If handpumps are already being used in the area and can be maintained, cast a slab to fit over the well to mount the pump. (Handpumps designed for bored wells can often be adapted.)

Simplest solution is often a pulley or windlass and a bucket which stays at the well.

Make sure everybody realizes how important it is to keep the well and its surrounds clean. Plant flowers and shrubs. It is advisable to fence the site.

The detail shows a tripod made of old rising mains with the ends flattened, bolted together, fitted with a pulley.

F

1. Watt, S. B. and Wood, W. E. *Hand dug wells and their construction*. Intermediate Technology Publications, London, UK, 1976.
2. DHV Consulting Engineers. *Shallow wells*, DHV Consulting Engineers, PO Box 85, Amersfoort, The Netherlands, 1978.

Compiled by Valerie Curtis. Illustrations by Frances Stuart.